

DCE-S 6/8 Plus

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238153

The main features

Precise temperature selection from 20 °C to 60 °C





Type	DCE-S 6/8 Plus	DCE-S 10/12 Plus
Part no.	238153	238154
Rated output	6,0/8,0 kW	10,0/12,0 kW
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm

Technical data

Rated voltage 1	220 V	220 V
Rated output 1	6,0/8,0 kW	10,0/12,0 kW
Rated current 1	27,3/36,4 A	45,5/54,5 A
Fuse 1	30/40 A	50/60 A
Frequency 1	50/60 Hz	50/60 Hz
Rated voltage 2	230 V	230 V
Rated output 2	6,6/8,7 kW	11,0/13,1 kW
Rated current 2	28,5/38,0 A	47,8/57,0 A
Fuse 2	30/40 A	50/60 A
Frequency 2	50/60 Hz	50/60 Hz
Rated voltage 3	240 V	240 V
Rated output 3	7,2/9,6 kW	12,0/14,3 kW
Rated current 3	30,0/40,0 A	50,0/59,5 A
Fuse 3	30/40 A	50/60 A
Frequency 3	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Temperature adjustment	20-60 °C	20-60 °C
Specific resistance $\rho_{15} \geq$	1100 Ω cm	1100 Ω cm

Specific conductivity $\sigma_{15 \leq}$	910 $\mu\text{S}/\text{cm}$	910 $\mu\text{S}/\text{cm}$
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	2,50 kg	2,50 kg

Expected to be available from June 2019

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.