

DCE-X 10/12 Premium

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238159

The main features

Fully electronic compact instantaneous water heater with 4i technology for maximum energy efficiency and accurate temperature delivery at all times

Temperature limit (childproofing)

Quick PROFI-RAPID installation

Suitable for reheating preheated water up to 55 °C (maximum inlet temperature 70 °C)





Type	DCE-X 6/8 Premium	DCE-X 10/12 Premium
Part no.	238158	238159
Rated output	6,0/8,0 kW	10,0/12,0 kW
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm

Technical data

Rated voltage 1	220 V	220 V
Rated output 1	6,0/8,0 kW	10,0/12,0 kW
Rated current 1	27,3/36,4 A	45,5/54,5 A
Fuse 1	30/40 A	50/50 A
Frequency 1	50/60 Hz	50/60 Hz
Rated voltage 2	230 V	230 V
Rated output 2	6,6/8,7 kW	11,0/13,1 kW
Rated current 2	28,5/38,0 A	47,8/57,0 A
Fuse 2	30/40 A	50/60 A
Frequency 2	50/60 Hz	50/60 Hz
Rated voltage 3	240 V	240 V
Rated output 3	7,2/9,6 kW	12,0/14,3 kW
Rated current 3	30,0/40,0 A	50,0/59,5 A
Fuse 3	30/40 A	50/60 A
Frequency 3	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C

Specific resistance $\rho_{15} \geq$	1100 Ω cm	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$	910 μ S/cm	910 μ S/cm
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	2,50 kg	2,50 kg

Expected to be available from June 2019

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.